













































































## Article 3 Community Design Standards

**Total Outdoor Light Output.** The initial total amount of light, measured in lumens, from all lamps used in outdoor light fixtures. Includes all lights and luminous tubing used for Class 1, Class 2, Class 3 and multi-Class lighting, and lights used for external illumination of signs, but does not include lights used to illuminate internally illuminated signs or luminous tubing used in neon signs. For lamp types that vary in their output as they age (such as high pressure sodium, fluorescent and metal halide), the initial lamp output, as defined by the manufacturer, is the value to be considered. For determining compliance with Section 3.7.060 of this Chapter, the light emitted from lamps in outdoor light fixtures is to be included in the total output as follows:

1. Outdoor light fixtures installed on poles (such as parking lot luminaires) and light fixtures installed on the sides of buildings or other structures, when not shielded from above by the structure itself as defined in parts 2, 3 and 4 below, are to be included in the total outdoor light output by simply adding the initial lumen outputs of the lamps;
2. Outdoor light fixtures installed under canopies, buildings (including parking garage decks), overhangs or roof eaves where all parts of the lamp or luminaire are located at least five (5) feet but less than ten (10) feet from the nearest edge of the canopy or overhang are to be included in the total outdoor light output as though they produced only one-quarter (0.25) of the lamp's rated initial lumen output;
3. Outdoor light fixtures installed under canopies, buildings (including parking garage decks), overhangs or roof eaves where all parts of the lamp or luminaire are located at least ten (10) feet but less than thirty (30) feet from the nearest edge of the canopy or overhang are to be included in the total outdoor light output as though they produced only one-tenth (0.10) of the lamp's rated initial lumen output.
4. Outdoor light fixtures installed under canopies, buildings (including parking garage decks), overhangs or roof eaves where all parts of the lamp or luminaire are located thirty (30) or more feet from the nearest edge of the canopy or overhang are not to be included in the total outdoor light output. Such lamps must, however, conform to the lamp source and shielding requirements of Section 3.7.050.